

LINEAR LOW MARBLED **POLYETHYLENE**

Description:

The marbled low density polyethylene compound was developed especially for rotomolded decorative pots, and it is available in three colors: Sand, Stone and Rust.

Applications:

Potted plants;

Technical parts and playgrounds;

Water reservoirs;

Technical specifications:

Smooth superficial and internal finishing;

Excellent processability;

Excellent balance between rigidity and resistance to impact;

Stabilization to heat and UV rays;



UV8 stabilization to weather and Antioxidants



EXAMPLE OF USE

Resin Properties:

TRIAL	METHOD	FIGURES	UNITY
Apparent Density	ASTM D 1895-96	0.420	g/cm3
Apparent Viscosity	ASTM D 1895-96	18	seconds
Melt flow index	D 1238	4	g/10min
Density	D 792	0.936	g/cm3
Impact resistance -40°C (Thickness 3.27mm)*	ARM	80	J

^{*}Rotomolded plaque

The information contained herein is provided in good faith, indicating average values obtained in our labs, and it should not be considered as absolute or as warranty. Only the properties and the values that are on the certificate should be considered as product warranty.



Website: www.grunplas.com.br

Contact:

+55 (45) 3253-8014 vendas1@grunplas.com.br

Rua Professor Evaldo Kissler, 151 — Parque Industrial Nova Santa Rosa — PR — Brazilian Industry

